

wire connector with control wire voltage tap-off 3 units accessory for:
3VA2 100/160/250



Model	
Product brand name	SENTRON
Product designation	accessories
Accessories	Wire connector
General technical data	
Designation / of the terminal	TA1.4
Connections according IEC	
IEC-marking / of terminals	16-185 mm ² CU/AL NNL
Connectable conductor cross-section	• for copper cable / stranded / minimum 16 mm² • for copper cable / stranded / maximum 185 mm² • for aluminum cable / solid / minimum 16 mm² • for aluminum cable / solid / maximum 16 mm² • for aluminum cable / stranded / minimum 16 mm² • for aluminum cable / stranded / maximum 185 mm²
Wire stripping length	20 mm

Tightening torque / when using copper cables	
• solid	16 mm²: 15.8 Nm
Connections according UL	
UL-marking / of terminals	TA1.4 CMC 6-350 CU7AL UR CSA
Permissible temperature / of connectable conductor / according to UL 486A-486B	75 °C
Wire stripping length	0.8 in
Connectable conductor cross-section	
• for copper cable / stranded / minimum	6 AWG
• for copper cable / stranded / maximum	350 kcmil
• for copper cable / finely stranded / minimum	6 AWG
• for copper cable / finely stranded / maximum	350 kcmil
• for copper cable / finely stranded / with core end processing / minimum	16
• for copper cable / finely stranded / with core end processing / maximum	120
• for aluminum cable / stranded / minimum	6 AWG
• for aluminum cable / stranded / maximum	350 kcmil
Tightening torque / when using copper cables	
• stranded	6 - 2 AWG: 140 lb-in, 1 AWG - 350 kcmil: 275 lb-in
• finely stranded	6 - 2 AWG: 140 lb-in, 1 AWG - 350 kcmil: 275 lb-in

Certificates

General Product Approval	EMC	Declaration of Conformity	Shipping Approval	other
Miscellaneous	 RCM	 EG-Konf.	 LRS	Manufacturer Declaration

other

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9263-0JG12>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA9263-0JG12>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA9263-0JG12

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



last modified:

05/06/2020