



Pohybový hlásič, PIR

**Typ
Catalog No.**

**CBMA-02/01
104921**

Dodavatelský program

Typ produktu			Senzor
Typ montáže			Povrchová montáž
Napájení			Baterie
Typ snímače			Pohyb Přítomnost

Technická data podle ETIM 7.0

Installation bus systems (EG000032) / Movement sensor for bus system (EC001582)			
Elektrotechnika, automatizační technika a technika řízení procesu / Elektroinstalacní zařízení, přístroj / Sbernicový systém / Movement sensor for bus system (ec1@ss10.0.1-27-14-31-44 [ACN421011])			
Bus system KNX			No
Bus system KNX radio			No
Bus system radio frequent			No
Bus system LON			No
Bus system Powernet			No
Other bus systems			xComfort
Radio frequent bidirectional			Yes
Model			Movement sensor
Mounting method			Surface mounted (plaster)
Material			Plastic
Material quality			Thermoplastic
Surface protection			Untreated
Surface finishing			Not applicable
Colour			White
RAL-number (akin)			9003
Transparent			No
Bus connection included			Yes
Substation input			No
Creep-under protection			No
Operation mode switch			Yes
Animal zone			No
Staircase monitoring			No
Response value luminosity adjustable			Yes
Teach-function for response value luminosity			No
Switch-off delay self-learning			No
Optimum mounting height		m	2.2
Max. transmission range sideways		m	12
Max. transmission range frontally		m	12
Diameter detection range on floor		m	12
Detection angle vertical		°	0 - 90
Detection angle horizontal		°	0 - 110
Number of channels			2
Number of binary inputs			0
Switching power		W	0
Min. switch-on time		s	30

Max. duty cycle	min	30
Min. depth of built-in installation box	mm	0

Další informace o produktech (propojení)

(IL019035ZU)Movement sensor PIR		
(IL019035ZU)Movement sensor PIR	https://es-assets.eaton.com/DOCUMENTATION/AWA_INSTRUCTIONS/MA136211013_2018_02.pdf	