



Propojovací svorka 16-70mm², 10 mm

Typ
Catalog No. **AKU70/10**
107193

Dodavatelský program

Sortiment			60mm systém 185mm systém Kompaktní systém
Základní funkce			Svorky
Dílčí sortiment			Univerzální připojovací svorky
Popis			s integrovanou pružinou, otevřenou připojovací mezerou a neztratitelným šroubem
Terminal area W x H		mm	14 x 14
Šířka		mm	20.5
Jmenovitý proud	le	a	400
Vodič			16 - 70 mm ² AWG 4 - AWG 2/0. přímo svorkovaná:   # 2x (3 x 9 x 0,8 mm) nebo 6 x 9 x 0,8 mm
Použitelné pro			All 10 mm thick flat busbars
Upozornění  round conductor, solid  Flexible, round conductor with correctly crimped ferrule Round conductor, stranded  Sector conductor, solid Sector conductor, stranded # CU band  CU busbar			

aprobace,

Product Standards			UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.			E307559
UL Category Control No.			NMTR2, NMTR8
CSA File No.			236217
CSA Class No.			3211-37
North America Certification			UL recognized, CSA certified
Conditions of Acceptability			Refer to approbation report
Specially designed for North America			No
Suitable for			Feeder circuits
Current Limiting Circuit-Breaker			Refer to approbation report
Max. Voltage Rating			600 V AC
Degree of Protection			Feeder circuits

