



Propojovací svorka 1.5-16mm², pro 5 mm

Typ **AKU16/5**
Catalog No. **107187**

Dodavatelský program

Sortiment			60mm systém Kompaktní systém
Základní funkce			Svorky
Dílčí sortiment			Univerzální připojovací svorky
Popis			s integrovanou pružinou, otevřenou připojovací mezerou a neztratitelným šroubem
Terminal area W x H		mm	7.5 x 7.5
Šířka		mm	11.5
Jmenovitý proud	le	a	180
Vodič			1,5 - 16 mm ² AWG 14 - AWG 6. přímo svorkovaná:    # 8 x 6 x 0,5 mm
Použitelné pro			All 5 mm thick flat busbars

Upozornění

 round conductor, solid

 Flexible, round conductor with correctly crimped ferrule

Round conductor, stranded

 Sector conductor, solid

Sector conductor, stranded

CU band

 CU busbar

aprobace,

Product Standards			UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.			E307559
UL Category Control No.			NMTR2, NMTR8
CSA File No.			236217
CSA Class No.			3211-37
North America Certification			UL recognized, CSA certified
Conditions of Acceptability			Refer to approbation report
Specially designed for North America			No
Suitable for			Feeder circuits
Current Limiting Circuit-Breaker			Refer to approbation report
Max. Voltage Rating			600 V AC
Degree of Protection			Feeder circuits

