



Rozpěrná svorka 95-185mm², pro 20x5-30x10

Typ **AKS185**
Catalog No. **107195**



Dodavatelský program

Sortiment			60mm systém 185mm systém
Základní funkce			Svorky
Dílčí sortiment			Rozpěrné svorky
Popis			Připojení ke sběrnicím bez vrtání děr Propojení kontaktů kabelů a propojovací lišty probíhá přes lože kabelu
Šířka		mm	38
Jmenovitý proud	I _e	A	500
Vodič			95 - 185 mm ² AWG3/0 - MCM350. directly terminated:   
Cu factor		kg	0,00
Použitelný pro			20 x 5/10 25 x 5/10 30 x 5/10
Použitelné pro			Double T profile
Upozornění			
○ round conductor, solid			
 Flexible, round conductor with correctly crimped ferrule			
Round conductor, stranded			
 Section conductor, solid			
Sector conductor, stranded			
# CU band			
 CU busbar			

aprobace,

Product Standards			UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.			E307559
UL Category Control No.			NMTR2, NMTR8
CSA File No.			236217
CSA Class No.			3211-37
North America Certification			UL recognized, CSA certified
Conditions of Acceptability			Refer to approbation report
Specially designed for North America			No
Suitable for			Feeder circuits
Current Limiting Circuit-Breaker			Refer to approbation report
Max. Voltage Rating			600 V AC
Degree of Protection			Feeder circuits

