



Připojovací svorkovnice, 35-120qm², 81 mm

Typ
Catalog No. BBA-TP3/120
107184



Dodavatelský program

Sortiment			60mm systém
Základní funkce			Svorky
Dílčí sortiment			Připojovací svorkovnice
Materiál			Bez silikonu, bez chlóru
Samozhášecí			podle UL 94
Odolnost proti plazivým proudům			CTI 200
Odolný proti teplotám			do 120°C
Popis			Odnímatelné svorky k připojení průchozích vodičů Okružování je možné
Terminal area W x H		mm	15 x 15
Šířka		mm	81
Póly			3
Jmenovitý proud	le	a	440
Vodič			35 - 120 mm ² AWG 2 - MCM 250.   # 10 x 16 x 0.8
Cu factor		kg	0,05
Použitelný pro			12 x 5/10 15 x 5/10 20 x 5/10 25 x 5/10 30 x 5/10
Použitelné pro			Double T profile
Upozornění			
○ round conductor, solid			
 Flexible, round conductor with correctly crimped ferrule			
Round conductor, stranded			
 Section conductor, solid			
Sector conductor, stranded			
# CU band			
 CU busbar			

aprobace,

Product Standards			UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.			E300273
UL Category Control No.			NMTR, NMTR7
CSA File No.			236217
CSA Class No.			3211-37
North America Certification			UL listed, CSA certified
Conditions of Acceptability			Refer to approbation report
Specially designed for North America			No
Suitable for			Feeder circuits
Current Limiting Circuit-Breaker			Refer to approbation report

Rozměry

