

DATOVÝ LIST - AKS1000



Rozpěrná svorka, 1000mm² pro 30x10 a T-profil

Typ
Catalog No.

AKS1000
107208



Dodavatelský program

Sortiment			60mm systém 185mm systém
Základní funkce			Svorky
Dílčí sortiment			Rozpěrné svorky
Popis			Připojení ke sběrnicím bez vrtání děr Propojení kontaktů kabelů a propojovací lišty probíhá přes spínací jednotku
Terminal area W x H		mm	55 x 28
Šířka		mm	72
Jmenovitý proud	le	a	1600
Vodič			do # (2 x) 10 x 50 x 1 mm do ■ (2x) 50 x 10 mm
Cu factor		kg	0,20
Použitelný pro			20 x 5/10 25 x 5/10 30 x 5/10
Použitelné pro			Double T profile
Upozornění ☐ round conductor, solid ☒ Flexible, round conductor with correctly crimped ferrule Round conductor, stranded ☐ Section conductor, solid Sector conductor, stranded # CU band ■ CU busbar			

aprobace,

Product Standards			UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.			E307559
UL Category Control No.			NMTR2, NMTR8
CSA File No.			236217
CSA Class No.			3211-37
North America Certification			UL recognized, CSA certified
Conditions of Acceptability			Refer to approbation report
Specially designed for North America			No
Suitable for			Feeder circuits
Current Limiting Circuit-Breaker			Refer to approbation report
Max. Voltage Rating			600 V AC
Degree of Protection			Feeder circuits

