



Propojovací modul pro neutrální vodič se zkušební zdírkou, 63A, 50/60Hz, 1HP



Typ Z-D63/P
Catalog No. 248268
Alternate Catalog No. Z-D63/P

Abbildung ähnlich

Technická data podle ETIM 7.0

Terminal blocks (EG000012) / Feed-through terminal block (EC000897)		
Elektrotechnika, automatizační technika a technika řízení procesu / Elektroinstalacní zařízení, přístroj / Svorka (mimo venkovní vedení) / Pruchozí svorka radová (ecl@ss10.0.1-27-14-11-20 [AFZ769018])		
Connectable conductor cross section fine-strand without cable end sleeve	mm ²	0 - 0
Connectable conductor cross section fine-strand with cable end sleeve	mm ²	0 - 0
Connectable conductor cross section solid-core	mm ²	1 - 25
Connectable conductor cross section multi-wired	mm ²	1 - 25
Rated current I _n	A	63
Rated voltage	V	230
Type of electrical connection 1		Screw connection
Type of electrical connection 2		Other
Connection position		Above
Number of levels		1
Number of clamp positions per level		1
Mounting method		DIN rail (top hat rail) 35 mm
Material insulation body		Other
Operation temperature	°C	-25 - 40
Inflammability class of insulation material acc. with UL94		Other
Width/grid dimension	mm	175
Height at lowest possible mounting height	mm	80
Length	mm	60
Explosion-tested version 'Ex e'		No
Closing plate required		No
Colour		Grey
Internally connected stages		No