



Přednostní relé, 250VAC, 1S, 3-8A, 1HP

Typ Z-LAR8-S
Catalog No. 248259

Abbildung ähnlich

Technická data podle ETIM 7.0

Devices for distribution board-surface mounting (EG000062) / Load shedding relay for distribution board (EC001655)		
Elektrotechnika, automatizační technika a technika řízení procesu / Elektroinstalací zařízení, přístroj / Modulární radový vestavený přístroj pro rozbočovací proudových okruhu / Load shedding relay for distribution board (ec1@ss10.0.1-27-14-23-32 [ACN383011])		
Rated voltage	V	250
Rated current Iu	A	3 - 8
Just-operate current	A	3 - 8
Max. time-delayed switch-off	ms	0
Max. continuous current	A	10
Number of contacts as normally open contact		1
Number of contacts as normally closed contact		0
Number of contacts as change-over contact		0
Rated current (control contacts)	A	1
Max. switching voltage (control contacts)	V	250
Max. switching power (control contacts)	VA	7.7
Electrical lifespan (control contacts)	c (contacts)	100000
Mechanical lifetime (control contacts)	c (contacts)	0
Max. electrical switching cycles	c/h	3600
Voltage type		AC
Mounting method		DIN rail
Width in number of modular spacings		1
Built-in depth	mm	60
Degree of protection (IP)		IP20