DATOVÝ LIST - XLST5F105



Kryt horní/dolní, 6 výřezů pro příruby, IP55,ŠxH=1000x500

Typ	**XLST5F105**
Catalog No.	**114694**

Powering Business Worldwide™

Dodavatelský program

Produktová řada			Řídicí centra XVTL
Základní funkce			Kombinované skříně
Funkce produktu			Příslušenství
Příslušenství			Podlahové plechy Stropní plechy
Samostatný přístroj/kompletní přístroj			Stavebnicový systém
Popis			s výřezy příruby Stropní plech s výřezy pro přírubu F3A
Materiál			Ocelový plech 1.25 mm
Vlastnosti povrchu			polyesterový práškový lak RAL 7035, světle šedá
Vhodné pro šířku			1000
Vhodné pro hloubku			500
stupeň krytí			IP55 (s kabelovou průchodkou F3A)
Otvory (počet)			6
Informace k rozsahu dodávky			včetně šroubů

Technická data podle ETIM 7.0

Cabinet enclosures (EG000011) / Top-/floor cover element (enclosure/switchgear cabinet) (EC000744)

Elektrotechnika, automatizacní technika a technika rízení procesu / Skrín, rám, konstrukce, nosic stavební skupiny / Prvky strechy (ovládací skrín) / Top cover/top cover element (electrical cabinet) (ecl@ss10.0.1-27-18-24-05 [ACN616011])

Suitable for roof planking			Yes
Suitable for bottom planking			Yes
Width		mm	1000
Height		mm	15
Depth		mm	500
Suitable for enclosure building width		mm	1000
Suitable for enclosure building depth		mm	500
Material			Steel
Surface finishing			Powder coating
Colour			Grey
RAL-number			7035
With de-aeration			No
Suitable for outdoor set-up			No
With cable entry			Yes

© 09/2020 by Eaton Industries GmbH