DATOVÝ LIST - CSAR3F3CY2202




Propojovací kabely, 3p, AC, spojka M12 úhlová, konec otevřený, D=2m

Powering Business Worldwide™

Typ	**CSAR3F3CY2202**
Catalog No.	**136262**
Alternate Catalog No.	**CSAR3F3CY2202**

Dodavatelský program

Základní funkce		Příslušenství
Příslušenství		Propojovací kabely
Délka	mm	2000
Obsazení kontaktů		 1 = Zelený 2 = Červený/Černý 3 = Červený/Bílý
Druh napětí		AC
Póly		3-pólové
Konstrukční typ, výstupní strana		Konec vedení volné
Konstrukční typ, vstupní strana		Spojka, zaúhlená
Pro použití s		
Pro použití s		AC senzory, 3 póly, M12

Ověření návrhu podle ČSN EN 61439

Technické údaje pro ověření konstrukce		
Provozní teplota okolí min.	°C	-25
Provozní teplota okolí max.	°C	70

Technická data podle ETIM 7.0

Sensors (EG000026) / Sensor-actuator patch cord (EC001855)		
Elektrotechnika, automatizacní technika a technika rízení procesu / Kabel, vedení / Datový kabel konfekcionovaný / Assembled sensor actuator-line (ecl@ss10.0.1-27-06-03-11 [AFR601003])		
Number of poles		3
Type of electrical connection, field-sided		M12
Type of plug-in contact, field sided		Female (bus)
Positioning cable feed, field-sided		Angled
Type of electrical connection, box-sided		Other
Type of plug-in contact, box-sided		
Positioning cable feed, box-sided		Other
Cable length	m	2
Material of cable sheath		Other
Halogen free		No
Colour cable sheath		Other
With LED indication		No
Screened		No
Type of cable		Multi-core
Vulcanize		No
Material contact body		Other
Material of contact surface		Other
Permitted cable outer temperature after assembling without vibration	°C	40 - 70
Permitted cable outer temperature during assembling/handling	°C	40 - 70
Rated current In	A	0
Rated voltage	V	0
Continuity resistor	mOhm	0
Degree of protection (IP)		Other

aprobace,

Product Standards			CE marking

© 10/2020 by Eaton Industries GmbH