DATOVÝ LIST - CSDR4A4CY2203-D

Propojovací kabely, 4p, DC, spojka M12 ploché, zástrčka (konektor) úhlová, D=3m

Typ	**CSDR4A4CY2203-D**
Catalog No.	**136315**
Alternate Catalog No.	**CSDR4A4CY2203-D**

Dodavatelský program

Základní funkce			Příslušenství
Příslušenství			Propojovací kabely
Délka		mm	3000
Obsazení kontaktů			
Druh napětí			DC
Póly			4-pólové
Konstrukční typ, výstupní strana			Konektor, zaúhlený
Konstrukční typ, vstupní strana			Spojka, přímá
Pro použití s			
Pro použití s			DC senzory, 4 póly, 2-, 3- nebo 4-vodičové připojení, M12

Ověření návrhu podle ČSN EN 61439

Technické údaje pro ověření konstrukce			
Provozní teplota okolí min.		°C	-25
Provozní teplota okolí max.		°C	70

Technická data podle ETIM 7.0

Sensors (EG000026) / Sensor-actuator patch cord (EC001855)			
Elektrotechnika, automatizační technika a technika řízení procesu / Kabel, vedení / Datový kabel konfekcionovaný / Assembled sensor actuator-line (ecl@ss10.0.1-27-06-03-11 [AFR601003])			
Number of poles			4
Type of electrical connection, field-sided			M12
Type of plug-in contact, field sided			Female (bus)
Positioning cable feed, field-sided			Straight
Type of electrical connection, box-sided			M12
Type of plug-in contact, box-sided			Male (plug)
Positioning cable feed, box-sided			Angled
Cable length		m	3
Material of cable sheath			Other
Halogen free			No
Colour cable sheath			Other
With LED indication			No
Screened			No
Type of cable			Multi-core
Vulcanize			No
Material contact body			Other
Material of contact surface			Other
Permitted cable outer temperature after assembling without vibration		°C	40 - 70
Permitted cable outer temperature during assembling/handling		°C	40 - 70
Rated current In		A	0
Rated voltage		V	0
Continuity resistor		mOhm	0
Degree of protection (IP)			Other

aprobace,

Product Standards			CE marking

© 10/2020 by Eaton Industries GmbH