DATOVÝ LIST - CSDS5A5CY2205



Propojovací kabely, 5p, DC, spojka M12 ploché, konec otevřený, D=5m

Powering Business Worldwide™

Typ	**CSDS5A5CY2205**
Catalog No.	**166986**
Alternate Catalog No.	**CSDS5A5CY2205**

Dodavatelský program

Základní funkce			Příslušenství
Příslušenství			Propojovací kabely
Délka		mm	5000
Obsazení kontaktů			 1 = Hnědý 2 = Bílý 3 = Modrý 4 = Černý 5 = Zelený/Žlutý
Druh napětí			DC
Póly			5-pólové
Konstrukční typ, výstupní strana			Konec vedení volné
Konstrukční typ, vstupní strana			Spojka, přímá
Pro použití s			
Pro použití s			DC senzory, IntelliView E75-DST4…, 5 pólů, M12

Ověření návrhu podle ČSN EN 61439

Technické údaje pro ověření konstrukce			
Provozní teplota okolí min.		°C	-25
Provozní teplota okolí max.		°C	70

Technická data podle ETIM 7.0

Sensors (EG000026) / Sensor-actuator patch cord (EC001855)

Elektrotechnika, automatizacní technika a technika rízení procesu / Kabel, vedení / Datový kabel konfekcionovaný / Assembled sensor actuator-line (ecl@ss10.0.1-27-06-03-11 [AFR601003])

Number of poles			5
Type of electrical connection, field-sided			M12
Type of plug-in contact, field sided			Female (bus)
Positioning cable feed, field-sided			Straight
Type of electrical connection, box-sided			Other
Type of plug-in contact, box-sided			
Positioning cable feed, box-sided			Other
Cable length		m	5
Material of cable sheath			Other
Halogen free			No
Colour cable sheath			Black
With LED indication			No
Screened			No
Type of cable			Multi-core
Vulcanize			No
Material contact body			Other
Material of contact surface			Other
Permitted cable outer temperature after assembling without vibration		°C	40 - 70
Permitted cable outer temperature during assembling/handling		°C	40 - 70
Rated current In		A	0
Rated voltage		V	0
Continuity resistor		mOhm	0
Degree of protection (IP)			Other

© 10/2020 by Eaton Industries GmbH