



Typ
Catalog No.
Alternate Catalog
No.

IZMX-MIL32C-F16-1
184208
65A2840G35



Dodavatelský program

Sortiment			Příslušenství
Accessories			Interlocks
Accessories			Mechanical interlock, fixed mounting
			Type 32
			For 3 circuit-breakers with the same or different frame size: interlock: 2 against 1 / max. 2 ON. Any one or two circuit-breakers can be closed at the same time. In addition, three IZMX-MIL-CAB... cable kits are required. Select the appropriate part no. for each circuit-breaker.
Použitelný pro			IZMX16... INX16...
Montážní jednotky			pevná montáž

Ověření návrhu podle ČSN EN 61439

Technické údaje pro ověření konstrukce			
Provozní teplota okolí min.		°C	-25
Provozní teplota okolí max.		°C	70

Technická data podle ETIM 7.0

Low-voltage industrial components (EG000017) / Mechanic interlock for switch (EC001044)			
Elektrotechnika, automatizační technika a technika řízení procesu / Nízkonapetová spínací technika / Komponenta pro nízkonapetovou spínací techniku / Mechanické blokování (ecI@ss10.0.1-27-37-13-03 [AKN341013])			
Auxiliary contacts, extendable			No
Number of contacts as normally closed contact			0
Number of contacts as normally open contact			0

