



Typ
Catalog No.
Alternate Catalog
No.

IZMX-RR230AD-40-1
184127
68D2806G62

Dodavatelský program

Sortiment			Příslušenství
Accessories			Trip indication / Reset options
Accessories			Remote reset
			The circuit-breaker is equipped with a mechanical trip indicator (red pin). After the remote reset coil is electrically actuated, the reclosing lockout can be reset. Cannot be combined with remote reset.
Jmenovité řídicí napětí	U _s	V	208 - 240 V AC 50/60 Hz 208 - 250 V DC
Použitelný pro			IZMX40...W IZMX40...F
Poznámky			Rozšiřující sada obsahuje potřebné svorky pro řídicí vedení SEC.

Ověření návrhu podle ČSN EN 61439

Technické údaje pro ověření konstrukce			
Provozní teplota okolí min.		°C	-25
Provozní teplota okolí max.		°C	70

Technická data podle ETIM 7.0

Low-voltage industrial components (EG000017) / Shunt release (for power circuit breaker) (EC001023)			
Elektrotechnika, automatizační technika a technika řízení procesu / Nízkonapetová spínací technika / Výkonový vypínač, výkonový rozpojovav (nízkonapetový) / Spoušť na pracovní proud (ecI@ss10.0.1-27-37-04-18 [AKF016013])			
Rated control supply voltage U _s at AC 50HZ	V		208 - 240
Rated control supply voltage U _s at AC 60HZ	V		208 - 240
Rated control supply voltage U _s at DC	V		220 - 250
Voltage type for actuating			AC/DC
Initial value of the undelayed short-circuit release - setting range	A		0
End value adjustment range undelayed short-circuit release	A		0
Type of electric connection			Flat plug-in connection
Number of contacts as normally open contact			0
Number of contacts as normally closed contact			0
Number of contacts as change-over contact			0
Suitable for power circuit breaker			Yes
Suitable for off-load switch			Yes
Suitable for motor safety switch			Yes
Suitable for overload relay			No