



Snímač pohybu

**Typ
Catalog No.**

**CBMD-02/01
300918**

Dodavatelský program

Typ produktu			Senzor
Typ montáže			Zabudovaný Povrchová montáž
Napájení			Baterie Síťové napájení
Typ snímače			Pohyb Přítomnost
Barva			Čistě bílá

Technická data podle ETIM 7.0

Installation bus systems (EG000032) / Movement sensor for bus system (EC001582)			
Elektrotechnika, automatizační technika a technika řízení procesu / Elektroinstalací zařízení, přístroj / Sbernicový systém / Movement sensor for bus system (ecl@ss10.0.1-27-14-31-44 [ACN42101])			
Bus system KNX			No
Bus system KNX radio			No
Bus system radio frequent			Yes
Bus system LON			No
Bus system Powernet			No
Other bus systems			xComfort
Radio frequent bidirectional			Yes
Model			Movement sensor
Mounting method			Other
Material			Plastic
Material quality			Thermoplastic
Surface protection			Untreated
Surface finishing			Matt
Colour			White
RAL-number (akin)			9010
Transparent			No
Bus connection included			Yes
Substation input			No
Creep-under protection			No
Operation mode switch			No
Animal zone			No
Staircase monitoring			No
Response value luminosity adjustable			Yes
Teach-function for response value luminosity			No
Switch-off delay self-learning			No
Optimum mounting height		m	2.5
Max. transmission range sideways		m	4
Max. transmission range frontally		m	8
Diameter detection range on floor		m	5
Detection angle vertical		°	90 - 90
Detection angle horizontal		°	90 - 90
Number of channels			2
Number of binary inputs			0
Switching power		W	0
Min. switch-on time		s	3
Max. duty cycle		min	120

Min. depth of built-in installation box	mm	20
---	----	----