



Integrovaná jednotka snímače pohybu

Typ
Catalog No.

CPAD-00/230
300920

Dodavatelský program

Typ produktu		Balené jednotky Ovládání Senzor
Typ montáže		Zabudovaný Zapuštěná montáž Povrchová montáž
Napájení		Baterie Síťové napájení
Aktivační funkce		Spínání
Typ snímače		Pohyb Přítomnost
Barva		Čistě bílá

Technická data podle ETIM 7.0

Installation bus systems (EG000032) / Switch actuator for bus system (EC001097)			
Elektrotechnika, automatizační technika a technika řízení procesu / Elektroinstalací zařízení, přístroj / Sbernicový systém / Sbernicový systém - aktor (ecl@ss10.0.1-27-14-31-25 [AKE293014])			
Bus system KNX			No
Bus system KNX radio			No
Bus system radio frequent			Yes
Bus system LON			No
Bus system Powernet			No
Other bus systems			xComfort
Radio frequent bidirectional			Yes
Mounting method			Flush mounted (plaster)
Width in number of modular spacings			3
Local operation/hand operation			No
With LED indication			Yes
Number of binary inputs			0
Max. switching power		W	2300
Output power		W	2300
Suitable for C-load			Yes
Max. number of switching contacts			1
Max. switching current		A	10
Rated current		A	10
Rated operating voltage		V	196 - 253
Different phases connectable			No
Bus connection included			Yes
Bus module detachable			No
Min. depth of built-in installation box		mm	18
Modular expandability			Yes
Degree of protection (IP)			IP20