

## Han 16A-M-s (33-48) wire protection



Part number	09 20 016 2616
Specification	Han 16A-M-s (33-48) wire protection
HARTING eCatalogue	<a href="https://b2b.harting.com/09200162616">https://b2b.harting.com/09200162616</a>

### Identification

Category	Inserts
Series	Han A®
Specification	Continuing marking

### Version

Termination method	Screw termination
Gender	Male
Size	32 A
With wire protection	Yes
Number of contacts	32
PE contact	Yes
Contact identification	33 ... 48
Details	You need two inserts for a complete assembly!

### Technical characteristics

Conductor cross-section	0.75 ... 2.5 mm <sup>2</sup>
Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	3
Rated voltage acc. to UL	600 V
Insulation resistance	≥10 <sup>10</sup> Ω
Contact resistance	≤1 mΩ
Limiting temperature	-40 ... +125 °C
Tightening torque	0.5 Nm
Mating cycles	≥500

### Material properties

Material (insert)	Polycarbonate
-------------------	---------------



Pushing Performance

## Material properties

Colour (insert)	RAL 7032 (pebble grey)
Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
Material flammability class acc. to UL 94	V-0
RoHS	compliant with exemption
RoHS exemptions	6c: Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	Yes
REACH SVHC substances	Lead

## Specifications and approvals

Specifications	EN 60664-1 IEC 61984
Approvals	DNV GL
UL / CSA	UL 1977 ECBT2.E235076

## Commercial data

Packaging size	1
Net weight	66.6 g
Country of origin	Germany
European customs tariff number	85366990