

# Eaton 112930

Catalog Number: 112930

Eaton Moeller series xPole - PF6/7 RCCB. PF6, 4 pole, In: 25 A, Icn: 6 kA, IΔN: 0.03 A, Type A, Pulse-current sensitive, Partly surge-proof 250 A, residential and commercial

## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Moeller series xPole - PF6/7 RCCB	112930  EAN 9007912938842
<b>Product Length/Depth</b>	<b>Product Height</b>
80 mm	71 mm
<b>Product Width</b>	<b>Product Weight</b>
70 mm	0.32 kg
<b>Compliances</b>	<b>Certifications</b>
RoHS conform	IEC/EN 61008
<b>Model Code</b>	
PF6-25/4/003-A	

## Delivery program

### Application

Residual current circuit breaker for residential and commercial applications  
xPole - Switchgear for residential and commercial applications

### Number of poles

Four-pole

### Tripping time

Non-delayed

### Amperage Rating

25 A

### Rated short-circuit strength

6 kA

### Fault current rating

30 mA

### Sensitivity type

Pulse-current sensitive

### Impulse withstand current

Partly surge-proof 250 A

### Type

PF6  
Residual current circuit breakers  
Type A

## Technical data - electrical

### Voltage rating

230 V AC / 400 V AC

### Rated operational voltage (U<sub>e</sub>) - max

400 V

### Rated insulation voltage (U<sub>i</sub>)

440 V

### Rated impulse withstand voltage (U<sub>imp</sub>)

4 kV

### Rated fault current - min

0.03 A

### Rated fault current - max

0.03 A

### Frequency rating

50 Hz

### Short-circuit rating

63 A (max. admissible back-up fuse)

### Leakage current type

A

### Rated residual making and breaking capacity

500 A

### Admissible back-up fuse overload - max

25 A gG/gL

### Rated short-time withstand current (I<sub>cw</sub>)

6 kA

### Surge current capacity

0.25 kA

### Test circuit range

184 V AC - 440 V AC

### Pollution degree

2

### Lifespan, electrical

4000 operations

## Technical data - mechanical

## Design verification as per IEC/EN 61439 - technical data

**Frame**  
45 mm

**Width in number of modular spacings**  
4

**Built-in width (number of units)**  
70 mm (4 SU)

**Built-in depth**  
69.5 mm

**Mounting Method**  
Quick attachment with 2 latch positions for DIN-rail IEC/EN 60715  
DIN rail

**Degree of protection**  
IP20, IP40 with suitable enclosure  
IP20

**Terminals (top and bottom)**  
Open mouthed/lift terminals

**Terminal capacity (solid wire)**  
1.5 mm<sup>2</sup> - 35 mm<sup>2</sup>

**Connectable conductor cross section (solid-core) - min**  
1.5 mm<sup>2</sup>

**Connectable conductor cross section (solid-core) - max**  
35 mm<sup>2</sup>

**Terminal capacity (stranded cable)**  
16 mm<sup>2</sup> (2x)

**Connectable conductor cross section (multi-wired) - min**  
1.5 mm<sup>2</sup>

**Connectable conductor cross section (multi-wired) - max**  
16 mm<sup>2</sup>

**Terminal protection**  
Finger and hand touch safe, DGUV VS3, EN 50274

**Busbar material thickness**  
0.8 mm - 2 mm

**Lifespan, mechanical**  
20000 operations

**Permitted storage and transport temperature - min**  
-35 °C

**Rated operational current for specified heat dissipation (In)**  
25 A

**Heat dissipation per pole, current-dependent**  
0 W

**Equipment heat dissipation, current-dependent**  
3.1 W

**Static heat dissipation, non-current-dependent**  
0 W

**Heat dissipation capacity**  
0 W

**Ambient operating temperature - min**  
-25 °C

**Ambient operating temperature - max**  
55 °C

## Design verification as per IEC/EN 61439

### 10.2.2 Corrosion resistance

Meets the product standard's requirements.

#### 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

#### 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

#### 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

### 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

### 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

### 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

### 10.2.7 Inscriptions

Meets the product standard's requirements.

## 10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be

Permitted storage and transport temperature - max

60 °C

Climatic proofing

25-55 °C / 90-95% relative humidity according to IEC 60068-2

evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Additional information

Accessories required

Z-HK 248432

Features

Additional equipment possible

## Zdroje

Certifikáty

DA-DC-03\_Pf6

Instalační návody

IL019140ZU

Residual current circuit breaker

**Fitted with:**

Interlocking device  
IS/SPE-1TE 101911

**Special features**

Maximum operating temperature is 55 °C:  
Starting at 40 °C, the maximum permissible continuous current decreases by 3% for every 1 °C  
Tripping signal contact for subsequent installation Z-NHK 248434

**Used with**

Residual current circuit breakers  
Type A  
PF6  
KLV-TC-4 276241 (Compact enclosure)  
Z-FW/LP 248296 (Remote control and automatic switching device)  
Z-RC/AK-4TE 101062 (sealing cover set)

**Katalogy**

[eaton-xpole-pf6-rccb-catalog-ca019034en-en-us.pdf](#)  
[eaton-xpole-pf7-rccb-catalog-ca019032en-en-us.pdf](#)

**Výkresy**

[eaton-circuit-breaker-xeffect-frcmm-rccb-dimensions.jpg](#)  
[eaton-xpole-pf6/7-rccb-3d-drawing.jpg](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. Všechna práva vyhrazena.

Eaton is a registered trademark.  
All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)