

Eaton 112933

Catalog Number: 112933

Eaton Moeller series xPole - PF6/7 RCCB. Residual current circuit breaker (RCCB), 40A, 4-pole, 30mA, type A



General specifications

| | |
|--|----------------|
| Product Name | Catalog Number |
| Eaton Moeller series xPole - PF6/7 RCCB | 112933 |
| EAN | Packing Unit |
| 9007912938873 | Case Pack |
| Gross Weight | Quantity |
| 10.495 kg | 30 |
| Width | Length |
| 180 mm | 385 mm |
| Volume | Height |
| 15.939 dm ³ | 230 mm |
| Product Length/Depth | ERP Name |
| 80 mm | SAP-UNITY |
| Product Width | Product Height |
| 70 mm | 71 mm |
| Product Weight | Certifications |
| 0.32 kg | IEC/EN 61008 |
| Compliances | |
| RoHS conform | |
| Model Code | |
| PF6-40/4/003-A | |

Delivery program

Application

Residual current circuit
breaker for residential and
commercial applications
xPole - Switchgear for
residential and commercial
applications

Number of poles

Four-pole

Tripping time

Non-delayed

Amperage Rating

40 A

Rated short-circuit strength

6 kA

Fault current rating

30 mA

Sensitivity type

Pulse-current sensitive

Impulse withstand current

Partly surge-proof 250 A

Type

PF6
Residual current circuit
breakers
Type A

Technical data - electrical

Voltage rating

230 V AC / 400 V AC

Rated operational voltage (U_e) - max

400 V

Rated insulation voltage (U_i)

440 V

Rated impulse withstand voltage (U_{imp})

4 kV

Rated fault current - min

0.03 A

Rated fault current - max

0.03 A

Frequency rating

50 Hz

Short-circuit rating

63 A (max. admissible back-up fuse)

Leakage current type

A

Rated residual making and breaking capacity

500 A

Admissible back-up fuse overload - max

25 A gG/gL

Rated short-time withstand current (I_{cw})

6 kA

Surge current capacity

0.25 kA

Test circuit range

184 V AC - 440 V AC

Pollution degree

2

Lifespan, electrical

4000 operations

Technical data - mechanical

Design verification as per IEC/EN 61439 - technical data

Frame

45 mm

Width in number of modular spacings

4

Built-in width (number of units)

70 mm (4 SU)

Built-in depth

69.5 mm

Mounting Method

Quick attachment with 2 latch positions for DIN-rail IEC/EN

60715

DIN rail

Degree of protection

IP20

IP20, IP40 with suitable enclosure

Terminals (top and bottom)

Open mouthed/lift terminals

Terminal capacity (solid wire)

1.5 mm² - 35 mm²

Connectable conductor cross section (solid-core) - min

1.5 mm²

Connectable conductor cross section (solid-core) - max

35 mm²

Terminal capacity (stranded cable)

16 mm² (2x)

Connectable conductor cross section (multi-wired) - min

1.5 mm²

Connectable conductor cross section (multi-wired) - max

16 mm²

Terminal protection

Finger and hand touch safe, DGUV VS3, EN 50274

Busbar material thickness

0.8 mm - 2 mm

Lifespan, mechanical

20000 operations

Permitted storage and transport temperature - min

-35 °C

Rated operational current for specified heat dissipation (In)

40 A

Heat dissipation per pole, current-dependent

0 W

Equipment heat dissipation, current-dependent

13.1 W

Static heat dissipation, non-current-dependent

0 W

Heat dissipation capacity

0 W

Ambient operating temperature - min

-25 °C

Ambient operating temperature - max

60 °C

Design verification as per IEC/EN 61439

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be

Permitted storage and transport temperature - max

60 °C

Climatic proofing

25-55 °C / 90-95% relative humidity according to IEC 60068-2

evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Additional information

Accessories required

Z-HK 248432

Features

Additional equipment possible

Zdroje

Certifikáty

DA-DC-03_Pf6

Instalační návody

IL019140ZU

Residual current circuit breaker

Fitted with:

IS/SPE-1TE 101911

Interlocking device

Special features

Maximum operating
temperature is 60 °C:
Starting at 40 °C, the max.
permissible continuous
current decreases by 2.5%
for every 1 °C
Tripping signal contact for
subsequent installation Z-
NHK 248434

Used with

KLK-TC-4 276241 (Compact enclosure)

Z-FW/LP 248296 (Remote control and automatic switching
device)

Z-RC/AK-4TE 101062 (sealing cover set)

Katalogy

[eaton-xpole-pf7-rccb-catalog-ca019032en-en-us.pdf](#)

[eaton-xpole-pf6-rccb-catalog-ca019034en-en-us.pdf](#)

Výkresy

[eaton-circuit-breaker-xeffect-frcmm-rccb-dimensions.jpg](#)

[eaton-xpole-pf6/7-rccb-3d-drawing.jpg](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. Všechna
práva vyhrazena.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)