


833 - Creta - UGR<17

Code: 150240-0041



Creta is a new recessed LED ceiling fixture in the backlight version that offers a totally innovative way to enlighten spaces. In addition to producing high brightness and uniform diffused light, it keeps energy consumption extremely low, reaffirming itself as the ideal luminaire for functional and general lighting applications. It's a luminaire with slim design and lenticular optics ideal in rooms requiring controlled light distribution and maximum visual comfort (UGR<17).



GENERAL INFORMATION

Article	833 - Creta - UGR<17
Code	150240-0041

DIMENSIONS AND WEIGHT

Length (mm)	595 mm
Width (mm)	595 mm
Height (mm)	39 mm
Weight (Kg)	1.98 kg

INSTALLATION

Recessed dimensions - Length (mm)	590 mm
Recessed dimensions - Width (mm)	590 mm


ELECTRICAL CHARACTERISTICS AND CONTROLS

Voltage (V)	230 V
Frequency (Hz)	50 Hz
Wiring	CLD-D-D
Control interface	DALI
Power factor	≥0.95
Insulation class	Class II
Controllability	Yes (External control)

833 - Creta - UGR<17

Code: 150240-0041

PHOTOMETRIC DATA



Lighting source	LED
CRI	80
Luminous flux (output) (lm)	3966 lm
Power absorption (total) (W)	30 W
CCT	4000 K
Luminous efficacy (lm/W)	132 lm/W
Unified glare rating UGR (EN 12464-1) (Reflectance coefficient: ceiling 0.7 - walls 0.5)	UGR<17 (in any situation). According to standard EN 12464.
Low Flicker	luminaire with very low flicker: evenly distributed light for greater visual safety.
Colour consistency	SDCM3
LED flux maintenance	50000 hr, L 80, B 20

MECHANICAL CHARACTERISTICS

Impact resistance rating (IK)	IK06
IP (vl)	40
IP (va)	20



833 - Creta - UGR<17

Code: 150240-0041

MATERIALS AND COLOURS


Housing	body in steel sheet and frame in aluminium.
Optics	secondary lenses in high-performance and anti-yellowing PMMA.
Colour	White
Equipment	Ceiling lighting fixture with external driver; it can be easily housed in false ceilings.

STANDARDS AND COMPLIANCE

Photobiological safety class	RG0
Markings and tests	CE
Reference standards	EN60598-1. With degree of protection according to EN60529.
Energy Label	E

WARRANTY

After sales warranty	5 yr
----------------------	------



DOWNLOAD

MOUNTS

AssemblyInstructions 833 03-23.pdf


DESIGNS

TechnicalDrawing 833.dxf




833 - Creta - UGR<17


Code: 150240-0041




600 EM power supply kit



595 Frame 600x600 h 70 mm



320 Cord



907 Springs