Code: 150240-39





Creta is a new recessed LED ceiling fixture in the backlight version that offers a totally innovative way to enlighten spaces. In addition to producing high brightness and uniform diffused light, it keeps energy consumption extremely low, reaffirming itself as the ideal luminaire for functional and general lighting applications.

applications.
It's a luminaire with slim design and lenticular optics ideal in rooms requiring controlled light distribution and maximum visual comfort (UGR<17).




		GENERAL INFORMATION
Article	833 - Creta - UG	R<17
Code	150240-39	
		DIMENSIONS AND WEIGHT
Length (mm)	595 mm	
Width (mm)	595 mm	
Height (mm)	39 mm	
Weight (Kg)	1.98 kg	
		INSTALLATION
Recessed dimensions - Length (mm)	590 mm	
Recessed dimensions - Width (mm)	590 mm	
		ELECTRICAL CHARACTERISTICS AND CONTROLS
Voltage (V)	230 V	
Frequency (Hz)	50 Hz	
Wiring	CLD	
Power factor	≥0.95	
Insulation class	Class II	

None



Controllability






Lighting source	LED
CRI	80
Luminous flux (output) (lm)	3688 lm
Power absorption (total) (W)	30 W
ССТ	3000 K
Luminous efficacy (lm/W)	123 lm/W
Unified glare rating UGR (EN 12464-1) (Reflectance coefficient: ceiling 0.7 - walls 0.5)	UGR<17 (in any situation). According to standard EN 12464.
Low Flicker	luminaire with very low flicker: evenly distributed light for greater visual safety.
Colour consistency	SDCM3
LED flux maintenance	50000 hr, L 80, B 20

MECHANICAL CHARACTERISTICS Impact resistance rating (IK) IK06 IP (vI) 40 IP (va) 20



PHOTOMETRIC DATA

Code: 150240-39



Housing	body in steel sheet and frame in aluminium.
Optics	secondary lenses in high-performance and anti-yellowing PMMA.
Colour	White
Equipment	Ceiling lighting fixture with external driver; it can be easily housed in false ceilings.

	STANDARDS AND COMPLIANCE
Photobiological safety class	RG0
Markings and tests	CE
Reference standards	EN60598-1. With degree of protection according to EN60529.
Energy Label	E

5 yr

WARRANTY

WARRANTI

MATERIALS AND COLOURS

DOWNLOAD

After sales warranty

MOUNTS

AssemblyInstructions 833 03-23.pdf

DESIGNS

TechnicalDrawing 833.dxf





Code: 150240-39

600 EM power supply kit

595 Frame 600x600 h 70 mm

320 Cord

907 Springs

